



# CONSUMERS CHOICE POS, INC.

Free FedEx/UPS Shipping

About Us

## Toll Free 1-877-699-5779

Outstanding Service - Bargain Prices - Best Selection

[Home](#)
[Receipt Printers](#)
[Bar Code Scanners](#)
[Touch Monitors](#)
[Bar Code Printers](#)
[Cash Drawers](#)
[Cordless Scanners](#)
[Card Readers](#)
[Pole Displays](#)
[POS Keyboard](#)
[Receipt Paper](#)
[Printer Ribbons](#)
[Current Specials](#)
[Contact Us](#)

Argox

Cognitive

Eltron

SATO

Zebra

CX400

## SATO CX400 Series Barcode Printer

SATO CX400 Thermal Transfer/Direct Thermal Barcode Printer

**Free** FedEx/UPS 3 Day Shipping to any Location in the 48 Contiguous United States.

### SATO CX400 Desktop Barcode Printer

The SATO CX400 Series barcode printer provides users with an ideal low-cost, low-volume labeling solution.

Introducing the SATO's latest desktop printer in the "Compact" series – CX400. With a 32-Bit high-speed RISC processor, it allows for maximum throughput directly from standard Windows® applications as well as from SATO's proprietary labeling software – SATO Label Gallery. With a small footprint, it also has a 2MB internal Flash ROM and 1MB DRAM.

Additional features include a maximum print speed of 4inch/sec and maximum printing length of 50inches (without any memory expansion). This new SATO CX400 also offers a flexible interface module – RS-232C and Centronics interface as a standard interface.

The CX400 not only boasts of a sleek look with its smooth lines but also of its sturdy chassis. Offering a superior print quality, the SATO CX400 is more than perfect for low volume printing needs. Designed with "ease of usage" in mind, its wide loading compartment makes it easy for media loading (5"OD label roll can be loaded).

**One Year Manufacturers Warranty**

#### Compatibility -

Like other SATO printers, the CX400 barcode printer also uses the SATO Command Language. This means you can simply add any barcode printer into existing applications, combining the level and capability of the various SATO barcode printer models to meet your changing needs.

#### Compact Design -

The portability and compact design of the SATO CX400 Series barcode printer allows them to fit-in anywhere - on a crowded work surface or at a busy ware house, distribution center, or at points of transaction...even on your desk next to your computer.

#### Economical Solution -

The CX400 barcode printer offers a low-cost printing solution for low volume applications. Speed of 4 inches-per-



SATO CX400 Barcode Printer

**\*\*DISCONTINUED\*\***

second and feature rich design will satisfy a wide spectrum of requirements.

#### Media Capacity -

Designed for ease of use, the SATO CX400 barcode printer is designed to accommodate a full 5" OD roll of media, reducing downtime and simplifying operation.

Backed by SATO's world class reputation for reliability, the CX400 Series barcode printers are ideal for the cost-conscious low-volume user.

### Sato CX400 Barcode Printer Specifications

<b>Printing Method:</b>	Thermal Transfer/Direct Thermal
<b>Print Resolution:</b>	203 dpi
<b>Print Speed:</b>	4 ips (100 mm/second)
<b>Media Width:</b>	Max. 4.69" (119 mm) /Min 0.87" (22 mm)
<b>Max. Print Width:</b>	4.1" (104 mm)
<b>Min Print Length:</b>	0.87" (22 mm)
<b>Max Print Length:</b>	45" (1143 mm)
<b>Max. Ribbon Size:</b>	4.4" (110 mm) W x 328 ft. (100 m) L; Face-Out
<b>Dimensions:</b>	7.76" W x 10.2" D x 6.5" H (197 mm W x 257 mm D x 164 mm H)
<b>Weight:</b>	8.09 lbs (3.67 kg)
<b>Memory:</b>	2 MB DRAM, 2 MB Flash ROM, 4 MB or 6 MB Optional Flash
<b>Processor:</b>	32-BIT
<b>Media:</b>	Roll-fed or fan-fold, die-cut or continuous direct thermal (thermal transfer) labels, synthetics, and tag stock with or without black mark, gap, or notch. Max. Caliper: 0.0075" (0.254 mm) Max. Roll Diameter: 5" (127 mm) Wind: Face-Out or Face-In
<b>Ribbon:</b>	Max. Roll Diameter: 1.41" (36 mm) Min. Core Diameter: 0.5" (12.7 mm) Wind: Face-Out
<b>Sensing:</b>	Adjustable transmissive sensor for gap. Reflective sensor for black mark. Automatic, programmable setting of top of form. Label present sensor - optional with label dispenser. Ribbon-out sensor
<b>Interfaces:</b>	Centronics Parallel

<b>Bar Code Symbolologies:</b>	<b>Elementary: UPC-A, UPC-E, EAN-8, EAN-13, Code 39, Code 93, Code 128, Codabar, MSI, Bookland, Industrial 2/5, Interleaved 2/5, Matrix 2/5, Postnet, UCC/ EAN 128, 2-Dimensional: PDF417, Maxicode</b>
<b>Fonts:</b>	<b>Bitmap - 12 proportional, mono-spaced and outline fonts (Code table 858). Scalable Internal CG Triumvirate® &amp; CG Times® fonts. Optional Downloaded TrueType® fonts, scalable from 8 to 72 points.</b>
<b>Barcode and Font Formatting:</b>	<b>360° rotation of barcodes and text, character expansion horizontally and vertically, sequential numbering, form overlay for high-speed editing of complex formats.</b>
<b>Graphic Support:</b>	<b>Printing &amp; storage of .PCX, .BMP format, SATO Hex/binary</b>
<b>Software:</b>	<b>Windows® Drivers (Windows® 95, 98, ME, NT4.0, 2000, XP) “Label Gallery Free” - Label Software - Printer Utilities</b>
<b>Electrical Requirements:</b>	<b>100-120VAC/200-240VAC, 50/60 Hz (± 1%) Agency Certifications: CE, UL, CSA, TÜV</b>
<b>Environmental Requirements:</b>	<b>Operating: 40° to 100°F (4° to 38°C) 30-80% RH, non-condensing Storage: -4° to 122°F (-20° to 50°C) Max. 85% RH, non-condensing ESD: 8kV</b>

---

[POS Receipt Printer](#) | [Barcode Scanner](#) | [Touch Screen Monitor](#) | [Cordless Barcode Scanner](#) | [USB Barcode Scanner](#) | [Cash Drawer](#)  
[Retail Pole Display](#) | [Barcode Printer](#) | [Barcode Software](#) | [POS Software](#) | [Popular POS Hardware](#) | [Barcode Slot Reader](#)  
[POS Keyboard](#) | [Magnetic Card Reader](#) | [Linear Image Barcode Scanner](#) | [Signature Capture](#) | [Portable Data Terminal](#)  
[POS Receipt Printer Paper](#) | [POS Receipt Printer Ribbon](#) | [Barcode Printer Label](#) | [Barcode Printer Ribbon](#)  
[Site Map POS](#) | [Site Map Barcode](#)



[Outstanding Customer Service](#)

[Terms and  
Conditions](#)

[Privacy Policy](#)   [Free Shipping](#)

©1998-2008 Consumers Choice POS,  
Inc.