

OPTIONS

AUTO-CUTTER

Labels are cut automatically off the roll, making any job easier and more efficient. (SLP-T400C/SLP-T403C)



RFID

Create radio frequency identification (RFID) labels on demand for a variety of operations.

- Frequency: 865 ~ 955MHz
- Transmit Power: 1W
- Modulation: ASK
- Air Protocol: GEN2
- Type: FHSS



RIBBON

The advanced technological spare ribbon helps to maintain and extend the life of the print head.



COLOR

Choose from a classic Ivory or distinguished Dark Gray



Optional value-added features

- Short label (minimal height of label up to 6mm) printing supported
- Smart detection of empty label (Detect empty label and leap over to next label automatically)
- Linerless printing
- Peeler and Dispenser (Optional)

SLP-T400 Specifications

Printing Method	Direct Thermal Printing / Thermal Transfer Printing
Resolution	203dpi(8dot/mm), Optional 300dpi(11.81dot/mm, SLP-T403)
Printing Speed	150mm / sec (6 IPS)
Printing Width	104mm
Printing Length	6 ~ 1,000mm(39.4")
Character	Alphanumeric Character : 95 Extended Character : 128 X 23 pages International Character : 32 Resident Bitmap Fonts : 10
Paper	Types Gap, Notch, Black Mark, Continuous, Fan-Fold Width 25~116mm(1~4.6") ID 25.4~38.1mm(1~1.5"), OD Max ϕ 130mm(5.1"), Max ϕ 220mm(External) Types Wax, Wax/Resin, Resin -----> Outside Type
Ribbon	Width 33~110mm(1.3~4.3") Length Max 300m Core ID 12.5mm, 25.4mm
Sensor	Transmissive sensor, Reflective sensor (Position adjustable), Ribbon-End, Head Open sensor 1D : EAN-8, EAN-13, Code 39, Code 93, Code 128, 12 of 5, ITF, Coda bar, UPC-A, UPC-E 2D : PDF417, QR code, Maxi code, Data Matrix
Bar Codes	SLCS, EPL II, ZPL II, DPL, CPL
Emulation Driver	Windows 9x/ME/2000/NT 4.0/XP(x32/x64)/WEPOS/ 2003 Server(x32/x64)/VISTA(x32/x64)
Interface	Standard : Serial / Parallel / USB (optional External Ethernet) Ethernet version : Serial / Ethernet / USB
Text Printing	Multiply, Bold, Reverse and Rotation Functions
Block Printing	Line, Box, Slope printing supported Overwrite, Exclusive or Delete mode supported
Graphic Template	PCX, BMP The label format can be stored in the printer & can be reused Variable, Counter can be used in template.
Receive Buffer	256 Kbytes
NV Image	64 Kbytes
Warranty	Printer Unit 12 Months Head 6 Months Auto Cutter(Optional) 6 Months
Power Supply	Input AC : 100~240V / 50~60Hz, 1.5A Output DC : 24V, 3.75A
Operating Safety	Temperature : 0~45°C UL, CSA, TUV
EMC	FCC Class A, CE Marking
Dimensions	214(W) X 310(L) X 200(H) mm
Weight	Approximately 5.7kg(Set 2.0kg)
Option	RFID, Auto Cutter, Peeler

This publication carries product description without obligation and is not to be seen as a firm offer. All specifications and design are subject to change without notice. February 2009

BIXOLON® www.bixolon.com

BIXOLON Headquarters

Address #A-5F, Digital Empire Building, 980-3, Yeongtong-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do, 443-702, Korea
Tel +82 (0) 31 218 5500 Fax +82 (0) 31 218 5589
E-mail sales@bixolon.com

BIXOLON America Inc.

Address 1210 E. 223rd street Suite #330 Carson, CA 90745
Tel +1 858 764 4580 Fax +1 310 522 9319
E-mail sales@bixolonusa.com

BIXOLON Germany GmbH

Address Tiefenbroicher Weg 35, 40472 Düsseldorf
Tel +49 (0) 211 68 78 54 0 Fax +49 (0) 211 68 78 54 20
E-mail sales@bixolon.de

BIXOLON Thermal Transfer Label Printer



a Better Solution
for your Business™

High-performance, High-reliability

SLP-T400



SLP-T400 Highlights


- **Enhanced Hardware provided**
 - Faster printing speed (6 inches per second, 150mm/sec)
 - High resolution (300 dpi optional) of printing (SLP-T403)
 - Wide range of ribbon rolls length from 74m to 300m
 - All in one interface card (Serial, Parallel, USB) Internal/External Ethernet, Interface card (Optional)
- **Advanced Firmware included**
 - 5 different languages supported (Programming languages) SLCS, EPL II, ZPL II, DPL, CPL
 - The label format can be stored in the printer and can be reused 2D barcode (Maxi code, PDF 417, QR Code, Data Matrix) Block printing (Line, Box, and Slope etc.)
 - 23 Code pages supported (included in the standard firmware)
- **User friendly Software Tools**
 - Device Font
 - Command Programming
 - User-defined Paper Size
 - Compatible Nice Label Program
 - Zoom Driver from A4 or Letter size to 4 inch size
 - Vector Font included
 - Unified Label Printer Utility

BIXOLON®



High-performance, High-reliability SLP-T400

The BIXOLON SLP-T400 is the most comprehensive, cost-effective model of industrial thermal transfer label printers in the marketplace today. The SLP-T400 is an ideal for a wide array of mission critical bar code labeling requirements including 2D, such as Maxicode, PDF417, QR Code and Data Matrix applications. In fact, where intricate two-dimensional bar coding is required for compliance labeling, small parts tracking, or product identification, the SLP-T400 has emerged as the printer of choice by large, multinational operations.



BIXOLON Label Printer SLP-T400 integrates easily into a variety of printing applications including;

- Warehousing
- Inventory control, Asset management
- Transfer / Distribution
- Outer box, Shipping, Delivery, Pallet
- Healthcare specimen labeling and patient tracking
- Retail product marking, Shelf labeling, Coupon and Receipt printing
- Transportation / Logistics
- Ticketing – Events entry tickets
- General industry & Manufacturing labeling requirements

MAIN FEATURES OF THE SLP-T400

Enhanced Hardware Features

The SLP-T400 features an advanced controller board, triple (Serial, Parallel, USB) all in one, and rugged, compact design. A32-bit microprocessor and 64Mbits SDRAM provides printing performance up to 6 inches per second.

WIDER RANGE OF RIBBON CAPACITY

The thermal transfer label printer SLP-T400 incorporates the ribbon mechanism and it facilitates ribbon loading by providing easy access to the mechanism

- Ribbon Width: 33~ 110mm (1.3~4.3")
- Core Diameter : 12.5mm, 25.4mm
- Ribbon Length : 74~300m
- Ribbon Type : Wax, Wax/Resin, Resin

EASY TO HANDLE MEDIA ROLL HOLDER


The SLP-T400 accommodates a maximum 5.1 inches (Max.ø 130mm) OD media roll using centralized alignment and this user-friendly design ensures proper loading and correct alignment for a variety of different media types

- Media Width : 25~116mm (1~4.4")
- Core Diameter : 25.4~38.1mm (1~1.5")
- Max Roll Diameter : 130mm (5.1")
- Media Type : Roll-fed or Fan-fold, Die-cut or Continuous and optional Linerless
- Media Sensor : Transmissive sensor, Reflective sensor (Position adjustable), Ribbon-End, Head Open sensor



ALL IN ONE INTERFACE

- Standard : Serial / Parallel / USB (optional External Ethernet)
- Ethernet version : Serial / Ethernet / USB



Advanced Firmware

Designed with the most popular programming languages, the BIXOLON SLP-T400 takes the lead in a new generation of thermal transfer label printers. The standard 16Mbit flash memory allows many formats and graphics to be stored in the printer. The system supports resident typographic fonts, international character sets, block printing, all popular barcode sets and 2-d symbology such as Maxi code, PDF 417, QR code and even Data Matrix.

5 DIFFERENT EMULATIONS

- SLCS / EPL II / ZPL II / CPL / DPL – automatic change!

SIMPLE-TO-OPERATE AND CONVENIENT DIP SWITCHES

- Most of printer conditions can be changed with easy-to-use dip switch setting

VARIOUS CODE PAGES

- 23 Code pages supported

Unified label printer utility program helps you select any of them as standard

VECTOR FONT INCLUDED

User friendly Software Tools


The SLP-T400 is supported by a rich pool of utility software. The powerful windows driver, easy-to-use label design program, Zoom driver, and Unified label printer utility program set the SLP-T400 apart from the competition. Advanced new software continues to be developed and is available for download. These make the users can design the label, download the firmware and the other printer settings more easily and with no changes to hardware settings.

FULL FEATURED WINDOWS DRIVER

- Device font supported
- Faster printing speed with standard font (10 kinds of English fonts and 5 kinds of Korean fonts)
- Various barcode font
- 1D : Coda bar, Code 128, Code 39, Code 93, EAN 8, EAN 13, I 2 of 5, UCC/EAN 128, UPC-A, UPC-E
- 2D : Maxi code, QR code, PDF 417, Data Matrix

USER-DEFINED COMMAND FONT

SMART Z-DRIVER



- Z-Driver transmits A4 and Letter size document to the printer in 4inch format

UNIFIED LABEL PRINTER UTILITY PROGRAM

MANUAL CALIBRATION SETTING MANAGER

- Manual-calibration of media detection can be used when the printer cannot detect a media gap (or black mark) even after auto-calibration has been executed

This easy-to-use, low-maintenance printer SLP-T400 reduces training requirements and operating costs, and provides flexible solutions through a variety of options and accessories.

All you need in one package!

- SLP-T400 or SLP-T400C
- An AC adapter with the power cord
- A roll of ribbon and label paper (sticker type) to get started printing right away
- A cleaning pen for the thermal print head
- A user's manual
- An installation CD including the drivers, all software programs, test samples and the user's guide book

