

مشخصات فنی سخت افزار Caller ID :

Line Interface	
Telephone Lines	Up to 5 loop start-lines (RJ-11 connections)
Registrations	FCC Part 68, CE Mark
Caller ID Performance	
CID5L-FS	
Transmission Standard	Bell 202 or V.23
Mode	Receive Only
Caller ID Decoding Capacity	Up to 5 incoming calls
Data Rate	1200 bits per second (bps)
Receive Sensitivity	-30 dBm
Data Link	Type 1 CID: Bellcore GR-30, ETSI ETS 300-659
Caller ID Performance	
CID5L-DT	
Transmission Standard	DTMF
Mode	Receive Only
Caller ID Decoding Capacity	Up to 5 incoming calls
Data Rate	10 digits per second
Receive Sensitivity	-30 dBm
Data Link	Type 1 CID: national DTMF-based standards
RS-232 Interface	
Mode	Full Duplex
Data Rate and Format	1200, N, 8, 1
Communications	Without handshake
USB Interface	
Mode	Full Duplex
Data Rate	Full Speed USB
Drivers	98SE, ME, 2000, XP, Apple 8/9, & Linux
General	
Serial Cable	9pin socket 1.5 m Cable (included)
Power Supply (CID5L-FS)	220 Vac to 12 VDC (included)
Power Supply (CID5L-DT)	220 Vac to 9 VDC (included)
Size	1.4"x 6.0" x 7.0" deep (3.6 x 15.2 x by 17.8 cm)
Weight	10 oz. (0.28 kg)
Operating Temperature Range	32° F to 122° F (0° C to 50° C)
Operating Humidity Range	10 to 90% noncondensing
Warranty	
	One year standard warranty